

## PeopleLink MCC DSP 200W

PeopleLink DSP is the ultimate choice for High Definition Audio signal processor. The most powerful HD audio available, it delivers full continuous presence meetings with Multi Location Voice conferencing and is ideal for local sound reinforcement. Highly scalable and flexible -PeopleLink's Multichannel Console DSP provides HD voice communications platform. This powerful, fault tolerant solution is ideal for the communication needs of large enterprises as well as Service providers looking to offer video conferencing services. Advanced design - This is the most powerful and up to date microphone Mixer, DSP and Amplifier available in the Industry today. It is Compact, Simple and extremely User-friendly allowing you to do Large scale Video Conferencing from a compact audio System.

Product Features		
Range	: Wide operating range of 300 feet	
Power Supply Safety	${f y}$ : Power Supply Unit with Short Circuit, Overload and Over Voltage Protection	
SMT SMT Circuit	: Surface Mount Technology (SMT ) Circuit	
Efficiency	: High efficiency of ~90%	
Current	: Very low quiescent current. Can run on inverter.	
Circuit	: Technology (SMT) Circuit Integrated Self-Protection Surface Mount	
Frequency lock	: Quartz-locked frequency	
Area of application	: Classrooms, Training Rooms	
Capacity	: 100 to 150 seater	
Chassis	: 19-Inch chassis 2U (Rack Mountable) DSP with Inbuilt amplifier with	
	wireless microphone System	





# Specifications

## WIRELESS MICROPHONE SYSTEM

Microphone Type	: UHF
Microphone Frequency Response	: 80 Hz-18KHz
Gain Control	: Separate gain controls for both the channels
LCD Display	: Frequency, Group, Antenna & Channel is displayed on the LCD in the receiver
Output	: Balanced XLR and Mixed Unbalanced 1/4" Outputs
Antennas	: Soft, Flexible rubberised antennas
Frequencies	: 5 non interfering frequencies available
Microphone Options	: 2 x Handheld/ 1 Handheld +1 Lapel / 2 x Lapel
Operating Range	: 300 Feet
Frequency type	: Quartz locked frequency

#### AMPLIFIER

Power output @ 8 ohms	: 2 X100w, Vcc= 24V DC
Minimum impedance	: 8 ohms @50W
Frequency response	: 20 Hz-20,000Hz
Operating supply voltage	: 8 V to 24 V
Туре	: Class D (Digital)
Frequency Range	: 30 Hz. to 16 KHz.
Automatic Echo Cancellation	: Yes
Automatic Gain Control	: Yes
Dynamic Noise Reduction	: Yes
Full Duplex	: Yes
MIX Out	: 1 X6.5mm
Balanced XLR out	: UHF

### **INTERFACE**

USB Interface for PC connectivity

Balanced 48v/12v phantom mic inputs

Line Input Line Output

Unbalanced MIC input

RS-232 for controlling

- : 1 x 2RCA
- : 1 x 2RCA
- : 1 x USB 2.0
- : 1x 6.5mm phono jack with gain controlle
- : 2x XLR ports with separate gain controller
- : 1x RS-232 audio controlling





#### Multi Channel Console DSP 200W

#### **MISCELLANEOUS**

Power Supply Unit (PSU)	: Power Supply Unit with Short Circuit, Overload and Over Voltage Protection
Application	: Classrooms, Training Rooms
Capacity	: 100 to 150
Shape of the room	: NA
Level of Management that uses the room	: NA

## **PACKAGING INFORMATION**

#### Components

#### : 19 inch chassis 2U (Rack Mountable) DSP withInbuilt

: Inbuilt Package Includes People Link Multi Channel Console DSP with built-in Amplifier, Wireless Handheld Microphone, Wireless Wireless Handheld Microphone, Wireless Lapel Lapel Microphone, USB 2.0x1, Cable, Stereo to Microphone, Amplifier, 30W Speakersx2 (Optional) 2 RCA Cablex2, 30W Speakersx2 (Optional)

**Package Includes** 

## **Ordering Information**

Part code

: PCU-MCC-DSP-AIO - 200W

#### **GLOBAL HEADQUARTERS**

Q3-A3, 10th Floor, Cyber Towers, Hitech City, Madhapur, Hyderabad - 500 081 (India) Phone: +91 (40) 66903959 / 60 Email: vc@peoplelinkvc.com

#### **INTERNATIONAL CONTACT NUMBERS**

USA:+1-321-2163070 UK:+44-20-35190197 Africa : +27-10-5001977 Australia: +61-29-0988367 Canada : +1-647-4964195 Middle East : +973-1-6199342

Follow us:  $(\mathbf{in}) (\mathbf{y}) (\mathbf{f}) (\mathbf{a}) (\mathbf{G}) (\mathbf{g})$  www.peoplelinkvc.com/social-presence

DISCLAIMER: PeopleLink Unified Communications Pvt. Ltd., All rights reserved. All third party trademarks / products mentioned (If any) are the property of their respedive owners. Product Images are for illustration purpose only. Actual product may vary due to product enhancements. All specifications are subject to change without notice; system specifics may vary.

PeopleLink Public Document | PeopleLink Unified Communications Pvt. Ltd. | ISO 9001:2015 & ISO/IEC 27001:2013 Certified Company.

