



PeopleLink iCam FHD 1080p 10X (H.264)

PeopleLink iCam FHD 1080p 10X (H.264) delivers instant real time, face-to-face experience through its powerful design that enhances your collaboration experience; it provides great productivity benefits to transform your business. iCam seamlessly connects with your PC / Laptop over USB, so now conduct your large room meetings more ideally, and capture real time speaker expressions and reactions and to effectively communicate with your dispersed teams, Partners & customers.

Product Features

➤ **Full Function USB Interface**

Full function USB interface, support audio, support compressed video output.

➤ **1080P Full HD**

2.07 million effective pixels high quality HD CMOS sensor, can reach maximum 1920 x 1080 high resolution and achieve quality image.

➤ **Ultra-high Frame Rate**

The output frame rate up to 30fps in 1080P.

➤ **Low-light**

High SNR of CMOS sensor combined with 2D and 3D noise reduction algorithm, effectively reduce the noise, even under low illumination conditions, picture can still keep clean and clear.

➤ **Remote Control**

Using RS232 all the parameters of the camera can be remote controlled by the high-speed communications.

Product Features

➤ **H.264 Slice/ H.264 SVC Support**

Support Slice and SVC encoding mode, adapts to video conference of advance USB application.

➤ **Dual stream**

Support two stream output (YUY2, MJPEG, H.264 each of both), reduce the host codec pressure

➤ **Dual power supply**



Product Specifications

Camera

Video System	: 1080P, 720P, 540P, 480P, 360P, 240P etc.
Sensor	: 1/2.7", CMOS, Effective Pixel: 2.07M
Scanning Mode	: Progressive
Lens	: f4.7mm ~ 46.3mm, F1.8 ~ F2.8
Optical Zoom	: 10X
Digital Zoom	: 16x
Minimal Illumination	: 0.5 Lux @ (F1.8, AGC ON)
Shutter	: 1/30s ~ 1/10000s
White Balance	: Auto, 3000K/Indoor, 4000K, 5000K/Outdoor, 6500K_1, 6500K_2, 6500K_3, One Push,
Backlight Compensation	: Support
Color Optimization	: Support
Digital Noise Reduction	: 2D&3D Digital Noise Reduction
Video S/N	: ≥55dB
Horizontal Field of View	: 55° Degrees
Vertical Field of View	: 42° Degrees
Diagonal Field of View	: 68° Degrees
Horizontal Rotation Range	: ±170°
Vertical Rotation Range	: -30° ~ 90°
Pan Speed Range	: 2.7° ~ 35.7°/s
Tilt Speed Range	: 2.7° ~ 31.5°/s
H & V Flip	: Support
Image Freeze	: Support
Number of Preset	: 255
Preset Accuracy	: 0.1°

Product Specifications

USB Featured

Operate System	:	Windows 7, Windows 8, Windows 10, Mac OS X, Linux, Android
Color System /	:	YUV 4:2:2 / H.264 / MJPEG
Video Format	:	H.264 AVC: max to 1080P@30fps H.264 SVC: max to 1080P@30fps MJPEG: max to 1080P@30fps
USB Video Communication Protocol	:	UVC 1.0
UVC PTZ	:	Support
Remote	:	IR Remote

Input/Output Interface

USB Interface	:	1xUSB2.0: Type B female jack
Communication Interface	:	1xRS232 In: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/Pelco-D /Pelco-P
Power Jack	:	JEITA type (DC IN 12V)/USB B type (DC IN 5V)

Generic Specification

Input Voltage	:	DC 12V
Current Consumption	:	0.5A (Max)
Operating Temperature	:	-10°C ~ 40°C (14°F ~ 104°F)
Storage Temperature	:	-40°C ~ 60°C (-40°F ~ 140°F)
Power Consumption	:	5W (Max)
MTBF	:	>30000h
Size	:	141.3mm x 153mm x 163.6mm
Net Weight	:	1.153 KG

PACKAGING INFORMATION

[Ordering Information](#)

PeopleLink iCam FHD 1080p 10X (H.264) : PPU-PVC-FHD-H264-10X

GLOBAL HEADQUARTERS

Q3-A3, 10th Floor, Cyber Towers, Hitech City,
Madhapur, Hyderabad - 500 081 (India)
Phone: +91 (40) 66903959 / 60
Email: vc@peoplelinkvc.com

INTERNATIONAL CONTACT NUMBERS

USA : +1-321-2163070	Africa : +27-10-5001977	Canada : +1-647-4964195
UK : +44-20-35190197	Australia: +61-29-0988367	Middle East : +973-1-6199342

Follow us:  www.peoplelinkvc.com/social-presence

DISCLAIMER: PeopleLink Unified Communications Pvt. Ltd., All rights reserved. All third party trademarks / products mentioned (if any) are the property of their respective owners. Product Images are for illustration purpose only. Actual product may vary due to product enhancements. All specifications are subject to change without notice; system specifics may vary.

PeopleLink Public Document | PeopleLink Unified Communications Pvt. Ltd. | ISO 9001:2015 & ISO/IEC 27001:2013 Certified Company.