



PeopleLink Cascade - 4C+

PeopleLink Cascade 4C+ Cascade is a conference audio controller. The 4C can be connected with active speaker interface and 4 omnidirectional microphones based on 2.4G wireless cascade. It also supports wireless handheld microphone local amplification, which is widely used in In large conferences, it can also be used normally in Conference rooms and entertainment venues.

Intelligent audio processing:

Adopting the latest audio voice processing technology, including digital audio processing, dynamic noise reduction processing, industry-leading 384ms echo cancellation, full-duplex voice calls, 360° omnidirectional pickup, etc. The effective pickup radius of a single omnidirectional microphone can reach 2m . Two-way, natural and smooth meetings can be conducted at the same time, giving users a high-quality

Product Features

- Support external active speakers
- Support conference communication software such inVC, skype, zoom etc.
- Removable wireless omnidirectional microphone



interface

- B type USB interface
- 6.5mm audio jack
- Antenna interface
- DC power interface

Wireless omnidirectional microphone

- Audio bandwidth is 100-16KHz
- Sensitivity: -38 dB 94dB
- SPL@1KHz Signal to noise ratio: 65dB
- 94dB SPL@1KHz, A-weight

Audio characteristics

- Digital audio processing
- 384ms echo cancellation technology
- Intelligent dynamic noise reduction
- Full duplex 360° pickup range
- The effective pickup range is 3 to 4 meters

Computer system required

- Windows 7 / Windows 10 /MacOS

Power Supply

- Host power adapter -12V2A
- Slave power adapter -5V/500mA

Button on mics

- Microphone mute button
- Speaker mute button
- Volume up/down button
- Slave switch button

Master LED light status

- Master red light is always on: under normal work .
- The speaker status indicator on master is on in green: Under normal work
- The speaker status indicator light on master is on in red: Speaker mute

Slave mics LED light status

Normal work: the green light is always on

Mute microphone: red light is always on

Low power: the red light of the speaker flashes

Volume adjustment: the mic green indicator flashes

Not connected normally: the green light flashes

Environmental requirements

- Temperature: 5°~44°
- Humidity: 20~85% (no condensation)
- Noise level: <48db
- Storage temperature: -10°~55°

Product parameter

Size: Master: 267*145*51mm

Single mic: 110*110*25mm

Weight: Master: 1044g , Singel mic: 236g

Color: Business black

Ordering Information

PeopleLink Cascade - 4C+

: PPU-PVC-AD-50WS-4C+

GLOBAL HEADQUARTERS

Q3-A3, 10th Floor, Cyber Towers, Hitech City,
Madhapur, Hyderabad - 500 081 (India)
Phone: +91 (40) 66903959 / 60
Email: vc@peoplelinkvc.com

INTERNATIONAL CONTACT NUMBERS

USA : +1-321-2163070
UK : +44-20-35190197

Africa : +27-10-5001977
Australia: +61-29-0988367

Canada : +1-647-4964195
Middle East : +973-1-6199342

Follow us:       www.peoplelinkvc.com/social-presence

DISCLAIMER: PeopleLink Unified Communications Pvt. Ltd., All rights reserved. All third party trademarks/ products mentioned (if any) are the property of their respective owners. Product Images are for illustration purpose only. Actual product may vary due to product enhancements. All specifications are subject to change without notice; system specifics may vary.

PeopleLink Public Document | PeopleLink Unified Communications Pvt. Ltd. | ISO 9001:2015 & ISO/IEC 27001:2013 Certified Company.