

## PeopleLink Multichannel All in One DSP

PeopleLink DSP is the ultimate choice for High Definition Audio signal processor. The most powerful HD audio available, it delivers full continuous presence meetings with Multi Location Voice conferencing over its 4 inputs and 2 output DSP, ideal for local sound reinforcement. Highly scalable and flexible - PeopleLink's Multichannel Console DSP provides HD voice communications platform. This powerful, fault tolerant solution is ideal for the communication needs of large enterprises as well as Service providers looking to offer video conferencing services. Advanced design - This is the most powerful and up to date microphone Mixer, DSP and Amplifier available in the Industry today. It is Compact, Simple and extremely User-friendly allowing you to do Large scale Video Conferencing from a compact audio System.

#### **Product Features**

**Range**: Wide operating range of 90 feet

Power Supply Safety: Power Supply Unit with Short Circuit, Overload and Over Voltage Protection

**SMT SMT Circuit** : Surface Mount Technology (SMT ) Circuit

**Efficiency** : High efficiency of ~90%

**Current**: Very low quiescent current. Can run on inverter.

**Circuit** : Technology (SMT) Circuit Integrated Self-Protection Surface Mount

Frequency lock : Quartz-locked frequency

Area of application : Classrooms, Training Rooms

**Capacity** : 40 to 60 seater

Chassis : 19-Inch chassis 2U (Rack Mountable) DSP with Inbuilt amplifier with

wireless microphone System



# Specifications

### **WIRELESS MICROPHONE SYSTEM**

Frequency type : Quartz locked frequency

Operating Range : 90 Feet

Microphone Options : 2 x Handheld / 1 Handheld +1 Lapel / 2 x Lapel

Frequencies : 5 non interfering frequencies available

Antennas : Soft, Flexible rubberised antennas

Output : Balanced Phoenix and Mixed Unbalanced 1/4" Outputs

LCD Display : Frequency, Group, Antenna & Channel is displayed on the LCD in the receiver

Gain Control : Separate gain controls for both the channels

Microphone Frequency Response : 80 Hz-18KHz

Microphone Type : UHF

#### **AMPLIFIER**

Power output @ 8 ohms : 2 X100W, Vcc= 24V DC

Minimum impedance : 8 ohms @100W

Frequency response : 20 Hz-20,000Hz

Operating supply voltage : 8 V to 24 V

Type : Class D (Digital)

#### **DIGITAL SIGNAL PROCESSOR**

Frequency Range : 30 Hz. to 16 KHz.

Automatic Echo Cancellation : Yes

Automatic Gain Control : Yes

Dynamic Noise Reduction : Yes

Noise Supression : Yes

Full Duplex : Yes

#### **INTERFACE**

Input : Built-In 1 x Handheld, 1 x Lapel Microphone

Unbalanced MIC input : 1x 6.5mm phono jack with gain controlle

Balanced 48v/12v phantom MIC inputs : 2x Phoenix ports with separate gain controller

Line input : 1 x 2RCA

Line Output : 1 x 2RCA

USB Interface for PC connectivity : 1 x USB 2.0

RS-232 for controlling : 1x RS-232 audio controlling



#### PeopleLink Multichannel All in One DSP 200W

#### **MISCELLANEOUS**

: Power Supply Unit with Short Circuit, Overload and Power Supply Unit (PSU)

Over Voltage Protection

**Application** : Classrooms, Training Rooms

Capacity : 50 to 100 Seater

Shape of the room : Any

#### **PACKAGING INFORMATION**

: 19 inch chassis 2U (Rack Mountable) with Inbuilt DSP Components

> : Inbuilt Package Includes People Link Multi Channel Console DSP with built-in Amplifier, Wireless Handheld Microphone, Wireless Lapel Microphone, USB 2.0x1, Cable,

Stereo to Microphone, 2 RCA Cable x2, 50W Speakers x2 **Package Includes** 



Front Side



Back Side



Lapel Microphone



Handheld Microphone



50W Speakers

## **Ordering Information**

: PCU-MCC-DSP-AIO - 200W Part code

#### **GLOBAL HEADQUARTERS**

Q3-A3, 10th Floor, Cyber Towers, Hitech City, Madhapur, Hyderabad - 500 081 (India) Phone: +91 (40) 66903959 / 60 Email: vc@peoplelinkvc.com

#### INTERNATIONAL CONTACT NUMBERS

USA:+1-321-2163070 Africa: +27-10-5001977 UK:+44-20-35190197 Australia: +61-29-0988367 Canada: +1-647-4964195 Middle East: +973-1-6199342









Follow us: (in) (y) (f) (D) (G+) (n) www.peoplelinkvc.com/social-presence

DISCLAIMER: PeopleLink Unified Communications Pvt. Ltd., All rights reserved. All third party trademarks / products mentioned (If any) are the property of their respedive owners. Product Images are for illustration purpose only. Actual product may vary due to product enhancements. All specifications are subject to change without notice; system specifics may vary.

PeopleLink Public Document | PeopleLink Unified Communications Pvt. Ltd. | ISO 9001:2015 &ISO/IEC 27001:2013 Certified Company.

